

## VAP11N Firmware Upgrade Guide

VAP11N is a professional 150M Mini WiFi Bridge, together with WiFi Repeater function, that is elaborately developed by HouTian Network, the original creation D/A temperature compensated auto frequency control technology (TAFC) , it solved the common failing of the traditional wifi router or wifi products that easily drop the network, make sure the lasting stability to ensure that the WiFi signal is not dropped. It is based on IEEE 802.11N standard, can extend WiFi Network range, provides the stable transmission up to 150Mbps, also is compatible with IEEE 802.11B and IEEE 802.11G standard. The following is introduced how VAP11N proceed to firmware upgrade:

The first step: VAP11N wired is connected to computer or laptop, mobile and other wireless devices connect to VAP11N wireless.

The second step: Open browser page



Ø Please enter <http://vonets.cfg> domain in browser, enter to login screen, then input user name and password, the default is admin, click Login to enter product configured page.

The third step: VAP11N configures to WiFi hotspot, connect Internet, the detailed steps, please follow the user manual operation. After configured to the hotspot successfully, please reboot VAP11N.

**Pay attention: Please use the browser above IE6.0 to configure and upgrade.**

The fourth step: Enter the browser page, click the System Settings —>Firmware Upgrade—>Upgrade, see the following picture:



Prompt: Please don't do any operations during upgrade process. If your VAP11N wifi bridge is the latest version, the following picture presentation will show:



**Attention:** After finishing the upgrade, please lastingly press the Reset button on the shell surface to restore the factory.

**Prompt:** During the configuration of VAR11N and VAP11N, the signal of source hotspot should be above 50%, if it is less than 50%, the signal will be weak and cause network poorly.